



Industrial ceiling fans				
	03.210	Industrial ceiling fan - white - height 69cm	Diameter 142cm, height 69cm, metal, 75W, 0,35A, 300rpm, performance max. 10m, safety screw connections, safety steel wire, color white	€ 148,00
	03.211	Industrial ceiling fan - black - height 69cm	Diameter 142cm, height 69cm, metal, 75W, 0,35A, 300rpm, performance max. 10m, safety screw connections, safety steel wire, color black	€ 148,00
	03.214	Industrial ceiling fan - height 44cm	Diameter 142cm, height 44cm, metal, 75W, 0,35A, 300rpm, performance max. 10m, safety screw connections, safety steel wire, color white	€ 148,00
	03.222	Industrial ceiling fan - IP54 - height 69cm	Diameter 142cm, height 69cm, metal, 75W, 0,35A, 300rpm, performance max. 10m, safety screw connections, safety steel wire, color white splash water protection IP54, stainless steel bearing	€ 196,20
	03.224	Industrial ceiling fan - IP54 - height 44cm	Diameter 142cm, height 44cm, metal, 75W, 0,35A, 300rpm, performance max. 10m, safety screw connections, safety steel wire, color white splash water protection IP54, stainless steel bearing	€ 196,20
	03.240	Industrial ceiling fan - HVLS - diameter 273cm	Diameter 273cm, height 70cm, 100W, 40-88rpm, performance max. 10m, massive all-metal construction, 6 cavity profile wing, 5-level remote control, forward and reverse run, safety steel wire, color metallic matte	€ 880,00
	03.260	Industrial ceiling fan - pipe clamp - tilt position	Diameter 95cm, height 42cm, metal, 65W, 0,3A, 340rpm, safety screw connections, safety steel wire, color white, suspension for tube 55-60mm, certificate for tilt position and increased ambient temperatures	€ 186,00

Industrial circulation fans				
	03.271	Industrial circulation fan - oscillation - remote control - 71cm	Grid diameter 71cm, 125W, installation on wall/internals, oscillation with start/stop during operation, brushless DC motor, highly energy efficient, wireless remote/wall control, fan group control, 6 speed + super gentle mode, timer, anti-lock, flat packed in two boxes	€ 279,50
	03.272	Industrial circulation fan - oscillation - remote control - 80cm	Grid diameter 80cm, 125W, installation on wall/internals, oscillation with start/stop during operation, brushless DC motor, highly energy efficient, wireless remote/wall control, fan group control, 6 speed + super gentle mode, timer, anti-lock, flat packed in two boxes	€ 313,60
	03.280	Industrial circulation fan - wall / ceiling - IP54 - 69cm	Grid diameter 69cm, 250W, 1,1A, 2-step speed control, installation on wall/ceiling/internals, 3-D-orientation, splash water protection IP54, completely assembled except the hanging parts	€ 338,00
	03.284	Industrial circulation fan - 56cm - oscillation - as 03.285 - pre-assembled	Grid diameter 56cm, 150W, 0,7A, installation on wall/tube/internals, 3-step speed control, oscillation, color black, single packed: completely assembled except the hanging parts, accessories: cross connector for tubes	€ 234,00
	03.285	Industrial circulation fan - 56cm - oscillation - as 03.284 - flat packed	Grid diameter 56cm, 150W, 0,7A, installation on wall/tube/internals, 3-step speed control, oscillation, color black, blades, guard and wall mounting packed separately, accessories: cross connector for tubes	€ 211,00


Industrial circulation fans				
	03.295	Industrial circulation fan - IP20 - vertical throw 20m	19Grid diameter 80cm, height 19cm, vertical throw 20m, 280W, 1,3A, 1350rpm, 2-step speed control, ceiling mounting material included, operation in any position, black, single packed and completely assembled	€ 289,00
	03.492	Mounting bracket for fan 03.295	Mounting bracket for the fan 03.295, for easy alignment of the fan in any position, set including mounting material, clamping handles and safety chain, for on-site installation	€ 32,80
	03.310	Industrial circulation fan - IP54 - vertical throw 14m	Grid diameter 69cm, height 20cm, vertical throw 14m, 250W, 1,1A, 1350rpm, 2-step speed control, ceiling mounting material included, operation in any position, black, single packed and completely assembled	€ 296,00
	03.312	Industrial circulation fan - IP54 - vertical throw 20m	Grid diameter 84cm, height 26cm, vertical throw 20m, 280W, 1,3A, 1350rpm, 2-step speed control, ceiling mounting material included, operation in any position, black, single packed and completely assembled	€ 427,00

Speed controller, stepless					
	03.403	Speed controller- stepless - manually	Illuminated main switch, minimum speed configurable, motor-friendly start-up phase configurable, surface-mounted, IP54 Suitable for fans 03.210-03.222, 03.260, 03.284-03.293	€ 98,60	
	03.404			0,3- 1,5 A	€ 105,45
	03.405			0,8- 3,0 A	€ 115,90
	03.406			1,3- 5,0 A 2,6-10,0 A	€ 178,00
	03.413 03.414 03.415 03.416	Speed controller - stepless - 0-10V-input	As before, but with 0-10V input for remote control. Without manual operation.	€ 178,70 € 193,30 € 216,90 € 235,40	

Speed controller, transformer regulator, 5-step					
	03.423	Speed controller - transformer regulator - 5-steps - manually	Manual 5-step control as well as ON/OFF switch with indicator light, output voltage and order is configurable, surface-mounted, IP54 Suitable for fans 03.210-03.222, 03.260, 03.280, 03.284-03.312	€ 168,90	
	03.425			2,2 A	€ 198,20
	03.426			5,0 A 7,5 A	€ 246,00
	03.407	Speed controller - transformer regulator - 5-steps - 0-10V-input	As before, but with 0-10V input for remote control. Without manual operation.	€ 307,00	
	03.408			3,5 A	€ 324,00
	03.409			5,0 A 7,5 A	€ 353,00

Speed controller, wireless remote, 16 channels				
	03.400	Remote control - 3-step - 16 fan groups - 1 hand transmitter and 1 receiver	Wireless remote control set. Hand-held transmitter with display and battery, u-shaped receiver for the fan upper canopy or for additional box on site, 16-channel codeable, up to 16 fan groups can be operated on one power cable. No combination with other control units. Suitable for one fan 03.210-03.224, 03.260	€ 46,80

Controller de-stratification				
	03.431	Controller recirculation warm air - 2 sensors - 4,0 A	De-stratification control for hall heating fans, display for temperatures and error messages, two temperature sensors included, IP54, 4A, amperage extension with a customary contactor	€ 297,00

Accessories				
	03.444	Ceiling hook for slant double t-beam	Ceiling hook for ceiling fans 03.210-03.224. Special shape for clips on slant double t-beam	€ 1,90
	03.450 03.451 03.452	Clip for double t-beam M6	Clip for double t-beam, M6x10, maximum load 45 kg Clamping range 3- 8 mm Clamping range 8-14 mm Clamping range 14-20 mm	€ 1,60 € 1,60 € 1,60
	03.453 03.454 03.455	Clip for double t-beam Eyelet	Clip for double t-beam, eyelet 6,5 mm, maximum load 90 kg Clamping range 3- 8 mm Clamping range 8-14 mm Clamping range 14-20 mm	€ 0,95 € 0,95 € 0,95
	03.494	Swivel arm	Swivel arm, arm length 0,75 - 1,10m, red, installation on tube 40-50mm or installation on wall, weight 9,5kg, maximum load 200kg	€ 44,30
	03.493	Cross connector for tubes	Cross connector 1-inch x 2-inch, galvanized, M8, with nuts, 230g for 03.284 / 03.285 at a tube 40-55mm	€ 7,40
	03.497	Safety chain	Safety chain additional for the fans 03.270 to 03.285, including chain 0,8m, 2 carabiners, wall plate (and eye bolt for 03.285)	€ 3,40

Packaging:

included

Pricing term:

All prices exclude VAT and shipping, ex warehouse Stemwede. Deliveries to EU countries are exempted from value-added tax on disclosure of the VAT ID.

Terms of payment:

Payment as agreed

Delivery to business customers only. Subject to change without notice. Offer non-binding. Subject to prior sale. Terms and conditions apply.