










Industrial ceiling fans

	03.210	Industrial ceiling fan - white - height 69cm	Diameter 142cm, height 69cm, metal, 75W, 0,35A, 300rpm, performance max. 10m, safety screw connections, safety steel wire, color white	€ 148,00
	03.211	Industrial ceiling fan - black - height 69cm	Diameter 142cm, height 69cm, metal, 75W, 0,35A, 300rpm, performance max. 10m, safety screw connections, safety steel wire, color black	€ 148,00
	03.214	Industrial ceiling fan - height 44cm	Diameter 142cm, height 44cm, metal, 75W, 0,35A, 300rpm, performance max. 10m, safety screw connections, safety steel wire, color white	€ 148,00
	03.222	Industrial ceiling fan - IP54 - height 69cm	Diameter 142cm, height 69cm, metal, 75W, 0,35A, 300rpm, performance max. 10m, safety screw connections, safety steel wire, color white splash water protection IP54, stainless steel bearing	€ 196,20
	03.224	Industrial ceiling fan - IP54 - height 44cm	Diameter 142cm, height 44cm, metal, 75W, 0,35A, 300rpm, performance max. 10m, safety screw connections, safety steel wire, color white splash water protection IP54, stainless steel bearing	€ 196,20
	03.240	Industrial ceiling fan - HVLS - diameter 273cm	Diameter 273cm, height 70cm, 100W, 40-88rpm, performance max. 10m, massive all-metal construction, 6 cavity profile wing, 5-level remote control, forward and reverse run, safety steel wire, color metallic matte	€ 780,00
	03.260	Industrial ceiling fan - pipe clamp - tilt position	Diameter 95cm, height 42cm, metal, 65W, 0,3A, 340rpm, safety screw connections, safety steel wire, color white, suspension for tube 55-60mm, certificate for tilt position and increased ambient temperatures	€ 177,00


Industrial circulation fans

	03.280	Industrial circulation fans - wall / ceiling - IP54 - 69cm	Grid diameter 69cm, 250W, 1,1A, 2-step speed control, installation on wall/ceiling/internals, 3-D-orientation, splash water protection IP54, completely assembled except the hanging parts	€ 338,00
	03.282	Industrial circulation fans - IP54 - oscillation - 81cm	Grid diameter 81cm, 150W, installation on wall/internals, oscillation, highly energy efficient, anti-lock, 4-step wall switch, splash water protection IP54, flat packed in two boxes	€ 313,60
	03.283	Industrial circulation fans - IP54 - oscillation - 71cm	Grid diameter 71cm, 140W, installation on wall/internals, oscillation, highly energy efficient, anti-lock, 4-step wall switch, splash water protection IP54, flat packed in 2 cartons	€ 279,50
	03.284	Industrial circulation fans - 56cm - oscillation - as 03.285 - pre-assembled	Grid diameter 56cm, 150W, 0,7A, installation on wall/tube/internals, 3-step speed control, oscillation, color black, single packed: completely assembled except the hanging parts, accessories: cross connector for tubes	€ 234,00
	03.285	Industrial circulation fans - 56cm - oscillation - as 03.284 - flat packed	Grid diameter 56cm, 150W, 0,7A, installation on wall/tube/internals, 3-step speed control, oscillation, color black, blades, guard and wall mounting packed separately, accessories: cross connector for tubes	€ 211,00
	03.291	Industrial circulation fans - as 03.293 - completely assembled	Grid diameter 81cm, height 34cm, vertical throw 16m, 260W, 1,1A, 1260rpm, 3-step speed control, ceiling mounting material included, operation in any position, color black. Single packed and fully assembled	€ 289,00
	03.293	Industrial circulation fans - as 03.291 - flat packed	Grid diameter 81cm, height 34cm, vertical throw 16m, 260W, 1,1A, 1260 rpm, 3-step speed control, ceiling mounting material included, operation in any position, color black. Blades, guard and motor packed separately to minimize volume.	€ 249,00


Industrial circulation fans

	03.310	Industrial circulation fans - IP54 - completely assembled	Grid diameter 69cm, height 20cm, vertical throw 14m, 250W, 1,1A, 1350rpm, 2-step speed control, ceiling mounting material included, operation in any position, black, single packed and completely assembled	€ 296,00
	03.312	Industrial circulation fans - IP54 - completely assembled	Grid diameter 84cm, height 26cm, vertical throw 20m, 280W, 1,3A, 1350rpm, 2-step speed control, ceiling mounting material included, operation in any position, black, single packed and completely assembled	€ 427,00


Speed controller, stepless

	03.403 03.404 03.405 03.406	Speed controller- stepless - manually	Illuminated main switch, minimum speed configurable, motor-friendly start-up phase configurable, surface-mounted, IP54 Suitable for fans 03.210-03.222, 03.260, 03.284-03.293 0,3- 1,5 A 0,8- 3,0 A 1,3- 5,0 A 2,6-10,0 A	€ 98,60 € 105,45 € 115,90 € 178,00
	03.413 03.414 03.415 03.416	Speed controller - stepless - 0-10V-input	As before, but with 0-10V input for remote control. Without manual operation. 0,3- 1,5 A 0,8- 3,0 A 1,5- 6,0 A 2,6-10,0 A	€ 178,70 € 193,30 € 216,90 € 235,40




Speed controller, transformer regulator, 5-stufig







	03.423 03.425 03.426	Speed controller - transformer regulator - 5-steps - manually	Manual 5-step control as well as ON/OFF switch with indicator light, output voltage and order is configurable, surface-mounted, IP54 Suitable for fans 03.210-03.222, 03.260, 03.280, 03.284-03.312 2,2 A 5,0 A 7,5 A	€ 168,90 € 198,20 € 246,00
---	----------------------------	---	---	----------------------------------

Speed controller, wireless remote, 16 channels

	03.400	<p>Remote control</p> <ul style="list-style-type: none"> - 3-step - 16 fan groups - 1 hand transmitter and 1 receiver 	<p>Wireless remote control set. Hand-held transmitter with display and battery, u-shaped receiver for the fan upper canopy or for additional box on site, 16-channel codeable, up to 16 fan groups can be operated on one power cable. Suitable for one fan 03.210-03.225, 03.260</p>	€ 46,80
---	--------	--	---	---------

More controllers

	03.431	<p>Controller recirculation warm air</p> <ul style="list-style-type: none"> - 2 sensors - 4,0 A 	<p>De-stratification control for hall heating fans, display for temperatures and error messages, two temperature sensors included, IP54, 4A, amperage extension with a customary contactor</p>	€ 297,00
	03.434	<p>Temperature control</p> <ul style="list-style-type: none"> - transformer regulator - 1 sensor - 5,0 A 	<p>Temperature control for summer ventilation, 5,0 A, transformer regulator, automatically depending on the temperature or manually in 5 steps, voltage configurable, 5,5kg, surface-mounted, IP54, 1m cable with temperature sensor Pt500</p>	€ 293,00
	03.436	<p>Interval switch</p> <ul style="list-style-type: none"> - 8,0 A 	<p>Interval switch for ventilation and drying applications, the working time and pause time can be defined between 3 and 60 minutes, surface-mounted, IP55-rail housing, 8 A</p>	€ 72,90

Accessories				
	03.444	Ceiling hook for slant double t-beam	Ceiling hook for ceiling fans 03.210-03.224. Special shape for clips on slant double t-beam	€ 1,90
	03.450 03.451 03.452	Clips for double t-beam M6	Clips for double t-beam, M6x10, maximum load 45 kg Clamping range 3- 8 mm Clamping range 8-14 mm Clamping range 14-20 mm	€ 1,60 € 1,60 € 1,60
	03.453 03.454 03.455	Clips for double t-beam Eyelet	Clips for double t-beam, eyelet 6,5 mm, maximum load 90 kg Clamping range 3- 8 mm Clamping range 8-14 mm Clamping range 14-20 mm	€ 0,95 € 0,95 € 0,95
	03.494	Swivel arm	Swivel arm, arm length 0,75 - 1,10m, red, installation on tube 40-50mm or installation on wall, weight 9,5kg, maximum load 200kg	€ 44,30
	03.495	Cross connector for tubes	Cross connector 2-inch x 3/4-inch, galvanized, M10, with nuts, 360g for 03.284 / 03.285 at a tube 40-55mm	€ 7,40
	03.497	Attachment for motor	Safety chain additional for the fans 03.280 to 03.285, including chain 0,8m, 2 carabiners, wall plate (and eye bolt for 03.285)	€ 3,40

Packaging:

included

Pricing term:

All prices exclude VAT and shipping, ex warehouse Stemwede. Deliveries to EU countries are exempted from value-added tax on disclosure of the VAT ID.

Terms of payment:

Payment as agreed

Open offer. Offer subject to prior sale. Terms and conditions apply.